

# HRS brand Heavy-Duty Commercial Ceiling Fan



- \* Completely Assembled (except blades). All metal construction. No plastic canopies or blades to burn, melt, or crack.
- \* Variable speed capacitor type, impedance protected, 18 pole "F" frame A/C motor. Cast aluminum motor housing.
- \* 3/4" od. x 18" steel downrod, frilled and clevis pinned to motor shaft.
- \* 3/8" x 7 1/4" steel J-type mounting hook with Spring Steel Safety Clip and Aircraft Type Lock-Nut to Prevent Spin-Off or Falling.
- \* 18/3 SJT Power Cord with Black Jacket & 3 Prong Molded Plug. 80 c. 10 amp, 120volt rateD, or wire leads.
- \* Factory Installed Type 304 Stainless Steel Internal Safety Cable, 7" x 1/16" diameter, 480# breaking strength.
- \* Self-locking 1/4" blade bolts with PVC Coated Threads.
- \* Heavy duty, high performance aluminum ribbed blades with vibration isolators.
- \* Tipped up end blades.

Model #	Diameter	Color	CFM	Airflow	Max R.P.M.	Coverage	Weight	Volts	Amps	Down Rod
L-156	56"	White	20,850	Down	310	2500 SQ. FT.	16 lbs	120	.70	16"
L-156-R	56"	White	20,850	Reversible	310	2500 SQ. FT.	16 lbs	120	.70	16"
L-156-B	56"	Brown	20,850	Reversible	310	2500 SQ. FT.	16 lbs	120	.70	16"
L-148	48"	White	16,850	Down	320	1500 SQ. FT.	15 lbs	120	.70	16"
L-148-R	48"	White	16,850	Reversible	320	1500 SQ. FT.	15 lbs	120	.70	16"
L-136	36"	White	10,700	Down	380	1000 SQ. FT.	12 lbs	120	.35	16"
L-136-R	36"	White	10,700	Reversible	380	1000 SQ. FT.	12 lbs	120	.35	16"



**Airdistributor**  
**PO Box 17815**  
**Indianapolis, IN 46217**  
**Ph 317-531-1638**  
**Fax 317-536-3390**