

HRS brand High Performance Industrial Ceiling Fans



- * Completely Assembled (except blades)
 - * Double Sealed Bearings
 - * Integral Bi-Metal **Firesafe**
 - * 7 Year Manufacturer's Warranty
 - * Self-Locking 1/4" Blade Bolts with PVC Coated Threads
 - * 18/3 SJT Power Cord with Black Jacket & 3 Prong Molded Plug
 - * Factory Installed Type 304 Stainless Steel Internal Safety Cable with 480# Breaking Strength
 - * Variable Speed Capacitor Type, Impedence Protected, 18 Pole "F" Frame A/C Motor
- *All Metal Construction
 - *1" od x 10" Downrod
 - *UL listed, CSA Approved
 - *Custom Colors Available

Model #	Diameter	Color	CFM	Airflow	Max R.P.M.	Coverage	Weight	Volts	Amps	Down Rod
L-360-AG	60"	White	43,500	Down	330	4800 SQ. FT.	25 lbs	120	.85	7"
L-360-18	60"	White	43,500	Down	330	4800 SQ. FT.	25 lbs	120	.85	18"
L-356-W	56"	White	34,500	Down	350	4200 SQ. FT.	24 lbs	120	.70	10"
L-356-B	56"	Brown	34,500	Down	350	4200 SQ. FT.	24 lbs	120	.70	10"
L-356-BL	56"	Black	34,500	Down	350	4200 SQ. FT.	24 lbs	120	.70	10"
L-356-240	56"	White	34,500	Down	350	4200 SQ. FT.	24 lbs	240	.35	10"
L-336-W	36"	White	12,000	Down	400	4200 SQ. FT.	--	120	.70	10"



Airdistributor
PO Box 17815
Indianapolis, IN 46217
Ph 317-531-1638
Fax 317-536-3390