

HRS brand Harsh Environment Industrial Ceiling Fan



- * Completely Assembled (except blades). All metal construction. No plastic canopies or blades to burn, melt, or crack.
- * Variable speed capacitor type, impedance protected, 18 pole "F" frame A/C motor. Cast aluminum motor housing.
- * Integral Bi-Metal **Firesafe** wired to line voltage with Automatic Shutdown (135 f) and Reset. Fire sensor to be mounted in the yoke cavity above and separate from the cast aluminum motor housing.
- * 3/4" od. x 16" steel downrod, frilled and clevis pinned to motor shaft.
- * 3/8" x 7 1/4" steel J-type mounting hook with Spring Steel Safety Clip and Aircraft Type Lock-Nut to Prevent Spin-Off or Falling.
- * 18/3 SJT Power Cord with Black Jacket & 3 Prong Molded Plug. 60 c. 10 amp, 120volt rate, or wire leads.
- * Factory Installed Type 304 Stainless Steel Internal Safety Cable, 7" x 1/16" diameter, 480# breaking strength.
- * Self-locking 1/4" blade bolts with PVC Coated Threads.

Model #	Diameter	Color	CFM	Airflow	Max R.P.M.	Coverage	Weight	Volts	Amps	Down Rod
S-560	60"	White	46,000	Down	320	5000 SQ. FT.	25 lbs	120	.85	16"
S-560-R	60"	White	46,000	Reversible	320	5000 SQ. FT.	25 lbs	120	.85	16"
S-560-277	60"	White	46,000	Down	320	5000 SQ. FT.	25 lbs	277	.30	16"
S-556	56"	White	27,500	Down	320	3800 SQ. FT.	24 lbs	120	.80	16"
S-556-R	56"	White	27,500	Reversible	320	3800 SQ. FT.	24 lbs	120	.80	16"
S-556-277	56"	White	27,500	Down	320	3800 SQ. FT.	24 lbs	277	.29	16"
S-548	48"	White	21,000	Down	350	3000 SQ. FT.	18 lbs	120	.55	16"
S-548-R	48"	White	21,000	Reversible	350	3000 SQ. FT.	18 lbs	120	.55	16"



Airdistributor
PO Box 17815
Indianapolis, IN 46217
Ph 317-531-1638
Fax 317-536-3390